

## SPECIFICATION SHEET FOR NH3 SENSOR TYPE NH3/MR-5000

### PERFORMANCE CHARACTERISTICS


Nominal Range	0 – 5000 ppm
Maximum Overload	ND
Expected Operation Life	2 years in air
Output Signal	5 ± 2 nA/ppm
Resolution	10 ppm
Temperature Range	- 10 °C to 50 °C
Pressure Range	Atmospheric <sup>1)</sup>
Pressure Coefficient	No data
T <sub>90</sub> Response Time	< 35 sec
Relative Humidity Range	15 % to 90 % R.H. non-condensing
Typical Baseline Range (pure air, 20°C)	0 ppm +/- 80 ppm
Maximum Zero Shift (+20°C to +40°C)	ND
Expected Long Term Output Drift	< 5 % signal loss per 6 month
Recommended Load Resistor	10 - 20 Ohm
Bias Voltage	Not allowed
Repeatability	< 3 % of signal
Output Linearity	< 5 % full scale
Humidity Effect	< 90 ppm

### PHYSICAL CHARACTERISTICS


Weight	~ 5.4 g
Position Sensitivity	None
Storage Life	Six months in container
Recommended Storage Temperature	5 °C – 20 °C
Warranty Period	12 months from date of dispatch

### Miniature-Size Outline Dimensions

BOTTOM VIEW



SIDE VIEW



### CROSS-SENSITIVITY DATA

Interfering Gas	Concentration	Reading
CO	300 ppm	0 ppm
H <sub>2</sub>	200 ppm	0 ppm
SO <sub>2</sub> <sup>3)</sup>	20 ppm	-7 ppm
H <sub>2</sub> S <sup>3)</sup>	20 ppm	7 ppm
NO <sup>3)</sup>	20 ppm	-1 ppm
NO <sub>2</sub> <sup>3)</sup>	20 ppm	-20 ppm
Cl <sub>2</sub>	20 ppm	-55 ppm
CO <sub>2</sub>	2 %	0 ppm

<sup>3)</sup> Long term exposures and high concentrations may affect the performance characteristics

Performance data conditions:  
20 °C, 50% RH and 1013 mbar

### APPLICATIONS

Discontinuous monitorin

The data contained in this document is for guidance only. Membrapor AG accepts no liability for any consequential losses, injury or damage resulting from the use of this document or the information contained within it. The data is given for guidance only. Customers should test under their own conditions, to ensure that the sensors are suitable for their own requirements.

REV.: 4/2014

Page 1 of 1

Phone: +41 43 311 72 00  
Fax : +41 43 311 72 01  
Email: info@membrapor.ch  
www.membrapor.ch

MEMBRAPOR AG  
Birkernweg 2  
CH-8304 Wallisellen  
Switzerland